

# 4000, 500, 6000 Fixed Picture WINDOW PERFORMANCE TABLE

Model	Style	VT	Metric U- Factor W/m <sup>2</sup> .k	Imperial U factor Btu/h ft <sup>2</sup> .F	Imperial R Value	SHGC	ER	Canada (Yes/No)	US Zones	NAF TEST RESULTS MAXIMUM SIZE TESTED
<b>4000, 5000, 6000 Series Fixed Picture</b>										
4020CLEAR	Fixed Picture	0.7	2.44	0.43	2.33	0.66	24			R-PG45, Size Tested (51 x 96)
4020CLEAR_GRIDS	Fixed Picture	0.63	2.44	0.43	2.33	0.6	21			R-PG45, Size Tested (51 x 96)
4020SOLR_GAIN	Fixed Picture	0.68	1.58	0.28	3.57	0.6	40	Y	N	R-PG45, Size Tested (51 x 96)
4020SOLR_GAIN_GRIDS	Fixed Picture	0.61	1.58	0.28	3.57	0.54	36	Y	N	R-PG45, Size Tested (51 x 96)
4020EVOLV	Fixed Picture	0.66	1.31	0.23	4.35	0.55	43	Y	N	R-PG45, Size Tested (51 x 96)
4020EVOLV_GRIDS	Fixed Picture	0.59	1.31	0.23	4.35	0.5	40	Y	N	R-PG45, Size Tested (51 x 96)
4020SOLR_SHIELD_PLUS_366	Fixed Picture	0.55	1.47	0.26	3.85	0.33	27		N, NC	R-PG45, Size Tested (51 x 96)
4020SOLR_SHIELD_PLUS_366_GRIDS	Fixed Picture	0.49	1.47	0.26	3.85	0.3	25		N, NC	R-PG45, Size Tested (51 x 96)
4020EVOLV_366_LOWE	Fixed Picture	0.54	1.23	0.22	4.55	0.23	26		N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020EVOLV_366_LOWE_GRIDS	Fixed Picture	0.48	1.23	0.22	4.55	0.21	25		N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020TRIPLE_CLEAR	Fixed Picture	0.64	1.65	0.29	3.45	0.6	38	Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_CLEAR_GRIDS	Fixed Picture	0.58	1.65	0.29	3.45	0.54	35	Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_1LOWE	Fixed Picture	0.62	1.19	0.21	4.76	0.51	43	Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_1LOWE_GRIDS	Fixed Picture	0.55	1.19	0.21	4.76	0.46	41	Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_2LOWE	Fixed Picture	0.59	0.91	0.16	6.25	0.48	48	Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_2LOWE_GRIDS	Fixed Picture	0.53	0.91	0.16	6.25	0.43	45	Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_EVOLV	Fixed Picture	0.6	1.02	0.18	5.56	0.49	46	Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_GAIN_EVOLV_GRIDS	Fixed Picture	0.54	1.02	0.18	5.56	0.44	43	Y	N	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_SHIELD_366_LOWE	Fixed Picture	0.5	1.17	0.21	4.76	0.22	27	Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020TRIPLE_SOLR_SHIELD_366_LOWE_GRIDS	Fixed Picture	0.45	1.17	0.21	4.76	0.2	26	Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020TRIPLE_EVOLV_SOLR_SHIELD_366_LOWE	Fixed Picture	0.49	1.01	0.18	5.56	0.21	30	Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020TRIPLE_EVOLV_SOLR_SHIELD_366_LOWE_GRIDS	Fixed Picture	0.44	1.01	0.18	5.56	0.19	29	Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_CLEAR	Fixed Picture	0.7	2.44	0.43	2.33	0.64	23			R-PG45, Size Tested (51 x 96)
4020_4MM_CLEAR_GRIDS	Fixed Picture	0.62	2.44	0.43	2.33	0.58	20			R-PG45, Size Tested (51 x 96)
4020_4MM_SOLR_GAIN	Fixed Picture	0.67	1.53	0.27	3.70	0.57	39	Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_SOLR_GAIN_GRIDS	Fixed Picture	0.6	1.53	0.27	3.70	0.51	36	Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_EVOLV	Fixed Picture	0.66	1.31	0.23	4.35	0.53	42	Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_EVOLV_GRIDS	Fixed Picture	0.59	1.31	0.23	4.35	0.48	39	Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_SOLR_SHIELD_PLUS_366	Fixed Picture	0.55	1.47	0.26	3.85	0.33	27		N, NC	R-PG45, Size Tested (51 x 96)
4020_4MM_SOLR_SHIELD_PLUS_366_GRIDS	Fixed Picture	0.49	1.47	0.26	3.85	0.3	25		N, NC	R-PG45, Size Tested (51 x 96)
4020_4MM_EVOLV_366_LOWE	Fixed Picture	0.53	1.22	0.22	4.55	0.23	26	Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_EVOLV_366_LOWE_GRIDS	Fixed Picture	0.48	1.22	0.22	4.55	0.21	25	Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_CLEAR	Fixed Picture	0.63	1.70	0.3	3.33	0.58	36	Y		R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_CLEAR_GRIDS	Fixed Picture	0.57	1.70	0.3	3.33	0.52	32			R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_1LOWE	Fixed Picture	0.61	1.25	0.22	4.55	0.49	41	Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_1LOWE_GRIDS	Fixed Picture	0.55	1.25	0.22	4.55	0.44	38	Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_2LOWE	Fixed Picture	0.59	0.97	0.17	5.88	0.46	45	Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_2LOWE_GRIDS	Fixed Picture	0.53	0.97	0.17	5.88	0.42	43	Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_EVOLV	Fixed Picture	0.6	1.08	0.19	5.26	0.47	43	Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_GAIN_EVOLV_GRIDS	Fixed Picture	0.53	1.14	0.2	5.00	0.43	40	Y	N	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_SHIELD_366_LOWE	Fixed Picture	0.5	1.19	0.21	4.76	0.22	26	Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_SOLR_SHIELD_366_LOWE_GRIDS	Fixed Picture	0.45	1.23	0.22	4.55	0.2	24		N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_EVOLV_SOLR_SHIELD_366_LOWE	Fixed Picture	0.49	1.04	0.18	5.56	0.21	29	Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)
4020_4MM_TRIPLE_EVOLV_SOLR_SHIELD_366_LOWE_GRIDS	Fixed Picture	0.44	1.07	0.19	5.26	0.19	27	Y	N, NC, SC, S	R-PG45, Size Tested (51 x 96)